

WHITE BLACK M: 25% Y: 100% M: 100% Y: 100%

CAUTION: Turn off power before use.

623-006



Listed as splicing wire connectors on the following stranded wire combinations: Voltage: 600V Max. Building Wiring; 1000V Max. Signs / Luminaries

- Strip stranded wires 14 mm (0.55").
- Pretwisting unnecessary.
Hold stripped wires together with ends even (lead stranded wires slightly).
- Align any frayed strands or conductors.
- Screw on connector—push wires firmly into connector when starting.
- To be sold only with installation instructions.

Winged Wire Connectors

Quantity: 100

- | | |
|---------------------|---------------------------|
| 2, 3 or 4 #18 | 1 #14 w/ 3 #18 |
| 1 #10 w/ 1 to 3 #18 | 1 #14 w/ 1, 2, 3 or 4 #16 |
| 1 #10 w/ 1 or 2 #16 | 2 #14 w/ 3 #18 |
| 1 #10 w/ 1 or 2 #14 | 2 #14 w/ 3 #16 |
| 1 #10 w/ 1 #12 | 3 #14 w/ 1 or 2 #18 |
| 1 #12 w/ 1 to 5 #18 | 3 #14 w/ 1 #16 |
| 1 #12 w/ 1 to 3 #16 | 2, 3, or 4 #16 |
| 1 #12 w/ 1 or 2 #14 | 1 #16 w/ 1 to 4 #18 |
| 2 #12 w/ 1 or 2 #18 | 2 #16 w/ 1 to 4 #18 |
| 2 #12 w/ 1 #16 | 3 #16 w/ 1 to 3 #18 |
| 2 #12 w/ 1 #14 | 4 #16 w/ 1 or 2 #18 |
| 2 or 3 #14 | |

LISTED FOR USE WITH
COPPER TO COPPER

Insulation operating temperature:
105°C (221°F) Max.



18-10 AWG; 600V Max. Building Wiring;
1000V Max. Signs / Luminaries



Made in China



63 mm

203 mm