

Totaline® Combustible Gas Detector P920-720B



Easily operate the P920-720B with one hand while detecting the presence of combustible gases including natural gas, methane, propane (LPG), gasoline, diesel, and kerosene. Pinpoint leak sources with its audible and visual indicators. An adjustable "tic" rate helps eliminate background gas concentration in contaminated environments.

Use the P920-720B to:

- Trace natural gas lines and fittings for leaks.
- Check gas applications for leaks.
- Check propane tanks, fitting lines, and heaters for leaks.
- Check gas generators for fuel leaks.
- Test confined spaces for gas build-up.

Features

- Instant response
- 10 ppm sensitivity
- Adjustable tic rate
- One-hand operation
- Visual and audible leak indication
- 16" gooseneck
- Soft carrying pouch
- 3-Year limited warranty

Instrument Specifications

Sensitivity:	10 ppm
Operating Temp:	32° to 104°F (0° to 40° C)
Warm-up:	7-10 seconds
Response Time:	Instantaneous
Battery:	3 "C" batteries
Battery Life:	20 continuous hours
Weight:	1.1 lbs.

Totaline® Digital Vacuum Gauge P920-605



Use the P920-605 to Verify the vacuum before you change a refrigerant system.

- Prevents moisture and air being left in the system.
- Finds small leaks.

Features:

- Measure vacuum from 25 to 0 microns
- Reads vacuum in seven international units of measure (Microns, PSI, InHg, mBar, Pascals, Torr, and mTorr)
- Display updates every 0.5 seconds
- Auto power off after 10 minutes when vacuum above 12,000 microns (12 Torr)
- Built in hook for hanging
- Cleanable sensor
- 300 PSI overpressure
- 3-Year limited warranty

Sensor Type	Thermistor
Connection Type	Standard 1/4" NPT male
Vacuum Range	0 - 12,000 microns (0 1600 Pascals)
Accuracy	10% of reading ±10 dgts
Units of Measure	Microns, PSI, InHg, mBar, Pascals, Torr, mTorr
Power Supply	9 volt alkaline battery
Operating Temp:	0° - 40°C (32° to 104°F)