## 811BH Small Diameter

APOLLOPRESS® Press End Copper Reducing Run Tee CxCxC (1/2"x1/2"x3/4")

# SUBMITTAL SHEET







| Job Name:        |  |
|------------------|--|
| Job Location:    |  |
| Engineer:        |  |
| Contractor:      |  |
| Tag:             |  |
| PO#:             |  |
| Rep:             |  |
| Wholesale Dist.: |  |

#### **DESCRIPTION**

The APOLLOPRESS® 811BH Small Diameter Press Reducing Run Tee features a lead free dezincification resistant copper body and an EPDM o-ring. APOLLOPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly made in the USA.

#### **FEATURES**

- · Lead Free Construction
- · Ridgid® XL Press Tool Compatible
- · Leak Before Press® Technology
- · Made in USA

#### **APPROVALS**

- UPC, cUPC & IPC
- IAPMO PS 117-2016 & TIL MSE-13
- · NSF/ANSI 61 Water Quality
- NSF/ANSI 372 Lead Free

#### PERFORMANCE RATING

- · Maximum Pressure: 300 psi
- Temperature Range: 32°F to 250°F depending on application

#### **APOLLOPRESS®**

- · Small Diameter Sizes 1/2"x1/2"x3/4"
- · Model 811BH, Reducing Run Tee


#### STANDARD MATERIALS LIST

| Body        | UNS C12200 Copper            |  |  |  |  |  |  |
|-------------|------------------------------|--|--|--|--|--|--|
| 0-Ring      | EPDM                         |  |  |  |  |  |  |
| Lubrication | Silicone, ANSI/NSF-61 Listed |  |  |  |  |  |  |

APOLLOPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

### **DIMENSIONS**

| ITEM NO. | MODEL 9 SIZE (IN )     | DIMENSIONS (IN.) |      |      |      |      |      |        |       |       | WT.   |
|----------|------------------------|------------------|------|------|------|------|------|--------|-------|-------|-------|
| HEMINO.  | MODEL & SIZE (IN.)     | Α                | A1   | В    | B2   | С    | C3   | HEIGHT | WIDTH | DEPTH | (LB.) |
| 10077810 | 811 ½x½x¾ CxCxC BH TEE | 1.71             | 0.96 | 1.71 | 0.96 | 1.49 | 0.59 | 1.99   | 3.41  | 1.23  | 0.330 |



\*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

