

8043W Series

Pro-Pal Union Ball Drain
Full Port Forged Brass Ball Valve
w/ Single Union End, Hi-Flow Hose Drain, Reversible Handle
& Adjustable Packing Glands
Press x FIP Union
Max Operating Pressure: 250 CWP
ISO 9001



Certified to NSF/ANSI 61-G & 372

ITEM#	SIZE (in)	Metric Pipe Size	CTN	CASE	A	B	C	D	E	F
80433W	3/4	0	4	16	0.75	4.32	2.63	3.50	2.50	0.50
80434W	1	0	2	16	1.00	4.80	2.63	4.65	2.50	0.50
80435W	1 1/4	0	2	8	1.25	5.20	2.63	4.65	3.00	0.75
80436W	1 1/2	0	1	5	1.50	6.20	3.30	5.50	3.15	0.75



NO.	DESCRIPTION	MATERIAL
1	Body	Lead Free Brass
2	End Cap	Lead Free Brass
3	Drain End Cap	Lead Free Brass
4	Ball	Lead Free Brass
5	Drain Ball	Lead Free Brass
6	Press End Connection O-Ring	EPDM
7	Seats	PTFE
8	Drain Seats	PTFE
9	Stem	Lead Free Brass
10	Drain Stem	Lead Free Brass
11	Packing Gland	PTFE
12	Drain Packing Gland	PTFE
13	Packing Nut	Brass
14	Drain Packing Nut	Brass
15	Handle	Steel CP
16	Drain Handle	Aluminum
17	Handle Nut	Stainless Steel
18	Drain Handle Fastener	Stainless Steel
19	Union Nut	Brass
20	Union Nut End Connection	Lead Free Brass
21	Union Nut O-Ring	EPDM
22	Drain Cap	Brass
23	Drain Cap Gasket	EPDM
24	Drain Cap Strap	PVC

Designed for residential, commercial or industrial use with water, oil or gas. This approved Webstone valve is actuated by a blowout proof stem and features an adjustable packing gland.

