



FORSAIRE™ COUNTERFLOW FURNACES



Building on the reliability of the gravity designed Monterey, the Forsaire Counterflow series features an integrated blower for floor-to-ceiling circulation of heat throughout the room or home. Optional outlet accessories allow it to heat up to three rooms.

TOP-VENT COUNTERFLOW

Models may be recessed into the stud space or surface-mounted and vented vertically through the ceiling and roof.

DIRECT-VENT COUNTERFLOW

Having a sealed combustion chamber, our Direct-Vent Counterflow Furnaces use only outside air for combustion. All by-products of combustion are discharged to the outside through the wall vent. All venting materials are included with these models.

FEATURES

- Free-standing or recessed mounting
- Multi-room heating with optional outlet kits
- Automatic temperature and safety controls

TOP & DIRECT-VENT MODEL FEATURES

- Natural or propane models (*conversions kits available*)
- "Matchless" pilot igniter
- Resettable vent-limit safety switch
- Equipped with a 4' electrical power cord

TOP-VENT
35,000 - 65,000
BTU/hr.

DIRECT-VENT
40,000 - 60,000
BTU/hr.



DESIGNED
& ASSEMBLED
IN THE USA
SINCE 1916



FORSAIRE™ COUNTERFLOW FURNACES

MODEL NUMBER		BTU/hr. INPUT	BTU/hr. OUTPUT	EFFICIENCY PERCENT		DIMENSIONS (INCHES)			BLOWER SPEED	CFM 115V	AMPS	PILOT TYPE	SHIPPING WEIGHT (LBS.)
NATURAL	PROPANE			THERMAL	AFUE	WIDTH	DEPTH	HEIGHT					
TOP-VENT COUNTERFLOW WITH ELECTRICAL POWER CORD													
NATURAL WITH CONVERSION KITS						STANDING PILOT							
3508632	3508632 + 7718	35,000	28,000	80	75.0	14 ⅞	10 ¾	72 ½	ONE	240	0.8	STANDING	90
5008632	5008632 + 7720	50,000	40,000	80	76.0	14 ⅞	10 ¾	81	TWO	350	2.2	STANDING	99
6508632	6508632 + 7726	65,000	48,000	74	76.0	14 ⅞	10 ¾	87	TWO	440	3.0	STANDING	107
NATURAL WITH CONVERSION KITS						INTERMITTENT IGNITION							
3508232	3508232 + 7716	35,000	28,000	80	75.0	14 ⅞	10 ¾	72 ½	ONE	240	0.8	INTERMITTEN	95
5508232	5508232 + 7722	55,000	42,500	77	76.0	14 ⅞	10 ¾	87	TWO	440	3.0	INTERMITTEN	113
DIRECT-VENT COUNTERFLOW WITH ELECTRICAL POWER CORD													
NATURAL WITH CONVERSION KITS						STANDING PILOT							
4007732	4007732 + 7728	40,000	32,000	80	75.4	14 ⅞	11 ¾	77 ⅞	ONE	325	2.0	STANDING	126
6007732	6007731	60,000	47,000	78	76.1	14 ⅞	11 ¾	87	TWO	440	3.0	STANDING	140
NATURAL WITH CONVERSION KITS						INTERMITTENT IGNITION							
4007332	4007331	40,000	32,000	80	76.5	14 ⅞	11 ¾	77 ⅞	ONE	325	2.0	INTERMITTEN	126
5507332	5507332 + 7730	55,000	42,500	77	76.5	14 ⅞	11 ¾	87	TWO	440	3.0	INTERMITTEN	140
Elevation rating from sea level to 2,000'						High altitude kits are available (see owner's manual)						1/2" Gas Connection	

Elevation rating from sea level to 2,000'

High altitude kits are available (see owner's manual)

1/2" Gas Connection

FEATURES

"MATCHLESS" PILOT IGNITER

All models include a "matchless" pilot igniter that assures convenient pilot lighting without matches.

CONTEMPORARY FINISH

Soft-white, powder-coat, heat-resistant finish to compliment any decor.

INTERIOR FURNACE CLEARANCES

- 4" to an intersecting wall.
- 4" from the top of the furnace to the ceiling or overhang.
- 2" from the top of the furnace to the ceiling or overhang on the 60088 series.
- 0" to finished floor.

IMPORTANT

ANY WARRANTY CONSIDERATIONS ARE CONTINGENT ON INSTALLATION BY A QUALIFIED INSTALLER (CONTRACTOR). SELF-INSTALLATION IS PROHIBITED AND WILL INVALIDATE YOUR WARRANTY.

- Read owner's manual before using/installing.
- Photographs are representative only.
- Check local codes and ordinances for permitted uses.
- Consult installation manual for clearances prior to installation.
- We reserve the right to amend product specifications without notice.
- Installation and servicing recommended by a qualified service person.
- Please read the warranty for any limitations of disclaimers. Combustion chamber carries a 10-year limited warranty. All other parts carry a one-year limited warranty.
- Venting must comply with the "Venting and Chimney Requirements" section of the instruction manual.
- Massachusetts Approval GI-0816-23, for top vents 6007731/6007732 is G3-0816-23 and for direct vents is G3-0218-317.



WARNING: This product can expose you to chemicals including epichlorohydrin which is known to the State of California to cause cancer and birth defects and/or other reproductive harm. For more information go to www.p65warnings.ca.gov



250 W. Laurel Street · Colton, CA 92324 USA

Subject to change without notice

© 2025 Williams

L1158_B 2-25

ACCESSORIES

THERMOSTAT SOLD SEPARATELY part number P322016

REAR AND SIDE OUTLET ACCESSORIES

Allows heat to be ducted into a rear or side room.

MODEL 6801 Rear-Outlet Register with 10" boot for Top-Vent models.

MODEL 6802 Rear-Outlet Register with 1" boot for Top-Vent models.

MODEL 6701 Side-Outlet Register with 10" boot for Top-Vent & Direct-Vent models.

MODEL 6702 Side-Outlet Grille for Top-Vent and Direct-Vent models.

FRONT DIFFUSING GRILLES

A snap on grille used to divert heat to the right, left, or in both directions.

MODEL 6703 Two-way directional diffuser grille for all models.

MODEL 6704 One-Way directional diffuser grille for all models.

VENTING ACCESSORIES

MODEL 4318 Vent Shield Deflector - insulated, galvanized metal sheet for Direct-Vent models.

MODEL 9307 Thin Wall Collar - wall thicknesses from 1" to 5". Used with Direct-Vent models.

MODEL 9308 Vent-Cap Guard - protects pedestrian traffic from the heat of the vent cap.

MODEL 9806 Direct-Vent Tube Extension - 12" length.

MODEL 9929 (USA) - Top-Vent Starter Kit - contains starter hold down plate, oval-to-round adapter, two spacer plates and two 2' lengths of oval pipe.

MODEL 9930 (CANADA) - Top-Vent Starter Kit - contains starter hold down plate, oval-to-round adapter, two spacer plates and two 2' lengths of oval pipe.

MODEL 9902 Vent Adapter for Top-Vent, free-standing (not recessed) installations.

TRIM STRIP ACCESSORY

MODEL 4701 Metal finishing strips painted the same color as the furnace for all models.

TOP-VENT ENCLOSURES

Used for free-standing installations. Includes two side rails and a metal cover painted soft-white to match the furnace.

MODEL 9812 12" - length

MODEL 9824 24" - length

MODEL 9836 36" - length

GAS CONVERSION KIT

7716

Natural Gas to Propane Gas for 3508232

7718

Natural Gas to Propane Gas for 3508632

7720

Natural Gas to Propane Gas for 5008632

7722

Natural Gas to Propane Gas for 5508232

7726

Natural Gas to Propane Gas for 6508632

7728

Natural Gas to Propane Gas for 4007732 and 4007332

7730

Natural Gas to Propane Gas for 5507332