Dehumidifier

Project: .	
------------	--

Architect:

Contractor:

Suppliers:

SPECIFICATIONS				
Capacity ⁽¹⁾	@ 80ºF/60% RH @ 73ºF/60% RH	130 ppd 105 ppd		
Energy Factor ⁽¹⁾	@ 80°F/60% RH @ 73°F/60% RH	2.9 L/kW-h 2.35 L/kW-h		
Airflow @ varying E.S.P. (external static pressure - dry coil)	0.0″ w.c. 0.2″ w.c. 0.4″ w.c	310 CFM 270 CFM 225 CFM		
Voltage, phase, frequency	120 VAC, 1 Phase, 60Hz			
Current draw ⁽¹⁾	7.7 Amps			
Noise	50 dBA ducted			
Dimensions (cabinet only) ⁽²⁾	Width: 19½" Height: 18³¼" Length: 30"			
Unit Weight Shipping Weight	98 lbs. 115 lbs.			
Leveling feet	Yes			
Control ⁽³⁾	Built-in digital control with display			
Control mounting	Field-interchangeable from top to front			
Cabinet insulation	1/2" EPS			
Air discharge orientation	Top or end			
Inlet/Outlet duct collars	10" dia.			
Backdraft damper at oulet	Included			
Filter	Washable MERV 8 (Part Number 5569)			
Refrigerant	R32			
Coil type	Corrosion-resistant aluminum			
8' Power cord	Yes			
Discharge air temperature rise	10°F-30°F			
Drain connection(4)	³ /4" MNPT Threaded			
Warranty	5 Years			

⁽¹⁾Rated capacity, energy factor and current draw measured at 80%/60%. RH inlet air at 0.0 ESP.
⁽²⁾Height does not include adjustable feet. The width excludes the filter doors and length excludes the duct collars.
⁽³⁾Builti-in automatic control capable to be set up for dehumidification and ventilation or zoning.
⁽⁴⁾ Threaded barbed fitting included



5-year warranty on all installed products

Intertek

(warranty does not apply to filters)

SUBMITTAL

Model E130W

Dehumidifier

Dealer:	
Engineer: _	
Location: _	
Date [.]	



OPERATION

The AprilAire Model E130W Wi-Fi Dehumidifier features Wi-Fi enabled technology which offers easy installation, setup, and pairing. The Aprilaire Model El30W Dehumidifier is designed to dehumidify the air coming into the unit by passing the incoming air over an evaporator coil, dropping the air temperature below the dew point. The moisture is removed from the air and drains out of the dehumidifier to a common floor or waste drain. The air is then reheated in the condenser coil and exits the unit.

Dehumidification occurs until the relative humidity (%RH) setting is reached. The unit then shuts off until periodic sampling determines the need for dehumidification. The integrated digital display and control monitors the %RH during sampling of the incompare reaction. incoming room or HVAC return air.

APPLICATION

AprilAire E130W Dehumidifier is the perfect product for whole-home dehumidification, basements, crawl spaces and sealed attics.

- The AprilAire Model E130W Wi-Fi Dehumidifier offers:
- Turn-Key Provisioning: Built-in control w/bluetooth
- Intuitive Controls: Enhanced, digital interface and app integration for ongoing monitoring and maintenance
- Integration with AprilAire Healthy Air App for alerts, diagnosis, and updates

VENTILATION

The E130W has the ability to bring in fresh, outdoor air into the living space. Fresh air Will dilute state air and pollutants and will reduce humidity in the winter months. If the humidity level of the outdoor air is higher than the %RH setting, the dehumidifier will begin dehumidification to reduce the humidity in the home to a set humidity level. The outdoor fresh air is brought in through a 6" round duct with a 6" round, normally closed damper. This complies with ASHRAE 62.2, Energy Star, and International Posidoatial Code (PC) Residential Code (IRC)

The dehumidifier has built-in controls to adjust the amount of fresh air that is brought in to the home. When properly installed and set, the model EI30W will meet the mechanical ventilation requirements of:

- ASHRAF 62.2
- Energy Star for Homes
- EPA Indoor airPLUS
- International Residential Code (IRC)
- International Energy Conservation Code (IECC)
- California Energy Commission Title 24

The submittal is intended to show general, overall product dimensions and provide guidance for installation clearance. Drawings are not to scale. Ensure submittals are current. AprilAire reserves the right to make product changes without notification or obligation.

Form No. Sub-E130W • 325428 • 04.25 © 2025 AprilAire | apriairepartners.com | 800.334.6011 AprilAire reserves the right to change specifications without notice.

DESIGNED & ASSEMBLED IN THE USA UTILIZING U.S. AND GLOBAL COMPONENTS