

# EZ-IN™ MINI-SPLIT CABLE

## 600 VOLT



600 Volt

90°C Dry

75°C Wet

Moisture and Sunlight Resistant

### APPLICATIONS Suitable for use as follows:

- Southwire's EZ-In™ Mini-Split Cable can be installed without the use of conduit and may be installed indoors and outdoors in wet locations

### STANDARDS & REFERENCES

- The National Electrical Code® / NFPA 70
- ASTM B3, B787
- UL Spec. No. 1569
- Rated for CT use
- Sunlight Resistant
- Direct Burial
- RoHS Compliant

### CONSTRUCTION

- Stranded bare copper THHN/THWN conductors with PVC insulation and Nylon jacket cabled together with an aluminum interlocking armor applied over the assembly
- A moisture and sunlight resistant, flame retardant PVC jacket is applied over the armor

### WEIGHTS, MEASUREMENTS, AND PACKAGING

SIZE (AWG)	NUMBER OF COND.	NUMBER OF STRANDS	INSULATION THICKNESS (PVC/NYLON) (mils)	JACKET THICKNESS OVER ARMOR (mils)	NOMINAL CABLE O.D. (mils)	NOMINAL WEIGHT (lbs/1000 ft)	CONDUCTOR COLORS
16	4	7	15/4	40	523	122	Black, Red, White, Green
14	4	7	15/4	40	553	148	Black, Red, White, Green
14	7	7	15/4	50	636	220	Black, Red, Blue, Orange, Yellow, Brown, Red-Black



greenSpec  
RoHS Compliant  
2002/95/EC