

# 95% Efficient!



**Burnham**  
by  
**U.S. Boiler Company**

**Burnham**

# Alpine™




## Gas Fired, Stainless Steel, Condensing Water Boiler

- 95% AFUE
- 80 – 399 MBH (6 sizes) 80-210 sizes are floor mount or wall hung – **SAME BOILER DOES BOTH!**
- Commercial models available, 399-800 MBH (5 sizes)  
Complete product info and specifications available separately
- Field-proven stainless steel heat exchanger
- Natural or LP gas
- Circulator included (80-285 models)
- 5-year part replacement warranty  
For residential boilers under 300 MBH



**Sage2.2™**  
boiler control system

- Backlit LCD touchscreen display provides diagnostic and troubleshooting information via intuitive text and menus, without cryptic codes or scrolling
- Full modulation with 5-to-1 turndown and adaptable firing rate output
- Outdoor reset included, plus warm weather shutdown, and off-season pump exercising
- DHW priority, control data logging, multiple & adjustable pump outputs
- 4-20mA and modbus inputs
- Compatible with optional Sage Zone Control Circulator Panel, which matches the boiler firing rates to actual zone load, saving money, energy, and preventing excessive boiler cycling



# Alpine: Technical Information



## Alpine Residential Standard Equipment

- Direct vent appliance
- Nylon floor guides
- Pre-installed hanging bracket and wall mount kit included
- Gas, water, electrical connections on left side of boiler
- Slide-out control panel
- Slide-out line voltage terminal strip
- Sage2.2 Control System
  - LCD touch screen display
  - Self-guided control menus
  - 100+ help screens
  - Built-in self diagnostics
  - (3) separate circulator outputs
  - Built-in sequencer, stages up to (8) boilers
  - 4-20 MV inputs for external control
  - Outdoor reset including wired outside sensor
  - DHW priority
  - Warm weather shutdown
- Variable speed combustion blower
- Natural or LP gas
- Negative pressure gas valve
- Stainless steel heat exchanger
- Boiler loop circulator
- Polypropylene condensate trap w/overflow protection
- Supply, return, and auto reset high limit water sensors
- 30 PSI safety relief valve
- Temperature and pressure gauge
- Flue gas temperature sensor and differential pressure switch
- CPVC to PVC vent kit
  - Includes 30" CPVC, 90° elbow, 2-vent terminals, screens,
- Five year parts replacement warranty

## Alpine Ratings & Specifications (sea level to 2000 feet)

Model	AFUE%	Input (MBH) min-max	DOE Heating Capacity (MBH)	Net AHRI (MBH)	Vent Size (Inches)	Approx. Shipping Weight. (lbs.)
MODELS FOR WALL OR FLOOR MOUNTING						
ALP080B	95.0	16-80	72	63	3	137
ALP105B	95.0	21-105	96	83	3	155
ALP150B	95.0	30-150	136	118	3	182
ALP210B	95.0	42-210	194	169	3	206
FLOOR MOUNTED MODELS						
ALP285B	95.0	57-285	262	228	4	256
ALP399C	94.1 <sup>1</sup>	80-399	375 <sup>2</sup>	326 <sup>3</sup>	4	316

<sup>1</sup>Thermal efficiency <sup>2</sup>Gross output <sup>3</sup>Net rating

### NOTES:

DOE Heating Capacity (ALP080 through ALP285); Gross Output (ALP399)  
 Safety Relief Valve Pressure, Water (ALP080B thru ALP285B) – 30 PSI std.; 50 PSI, 80 PSI, and 100 PSI optional  
 Safety Relief Valve Pressure, Water (ALP399 only) - 50 PSI std.; 80 PSI and 100 PSI optional  
 ASME certified 150 PSI Maximum Allowable Working Pressure at 210°F.  
 Max allowable temperature setting 210°F  
 Target setpoint is 190°F, automatic reset high limit setpoint is 200°F and manual reset high limit setpoint is 210°F  
 Boilers shipped set for natural gas; field adjustment for LP (see instruction manual)  
 For elevations above 2000 feet, reduce ratings four percent (4%) per 1000 feet above sea level

### Optional Equipment:

- LWCO kit (P/N: 100592-01)
- Sage Zone Control
  - Circulator Panel (P/N: 104590-01)
  - Valve Panel (P/N: 104589-01)
- Service parts repair kit (P/N: 105319-04)

### Alpine Vent & Intake Sizes

Model	Intake Size	Vent Size	Max Length Intake/Vent
ALP080B	2"	2"	60'/60'
	3"	3"	135'/135'
ALP105B	2"	2"	60'/60'
	3"	3"	135'/135'
ALP150B	3"	3"	135'/135'
ALP210B	3"	3"	135'/135'
ALP285B	3"	3"	60'/60'
	4"	4"	100'/100'
ALP399	4"	4"	100'/100'

Additional approved options

### Alpine Dimensions (inches)

Model	A	F	G	H	M
ALP080B	12-9/16	1/2	1	1	32-3/16
ALP105B	14	1/2	1	1	32-3/16
ALP150B	19-11/16	1/2	1	1	32-3/16
ALP210B	23-15/16	1/2	1	1	32-3/16
ALP285B	21-13/16	3/4	1-1/4	1-1/4	43-7/16
ALP399	28-7/8	3/4	1-1/2	1-1/2	43-7/16

