

Pro-Poly™ Eazy Flex Riser



PEFR SERIES

APPLICATION

The Pro-Poly™ PEFR Series Anodeless Gas Riser is for use in Natural and LP (Propane) underground gas applications utilizing Polyethylene (MDPE) gas pipelines. Meets or exceeds ASTM D2513 Category 1 and ASTM F1973 specifications.

| ITEM # SUBMITTED: | |
|-------------------|--|
| JOB NAME: | |
| LOCATION: | |
| ENGINEER: | |
| CONTRACTOR: | |
| PO #:_ | |
| TAG: | |
| | |

INSTALLATION

Product installation and system testing shall be in accordance with all applicable local codes and the Pro-Poly Installation Guide.

MATERIAL SPECIFICATIONS

Fitting: Carbon steel A29M, Zinc plated yellow dichromate

Pipe Threads: ASTM B117

Protectective Conduit: Galvanized Steel with Gray PVC Coating

O-Ring: EPDM Rubber

Grip Ring: High Hardness POM (Acetal) Thermoplastic APROVED GASES: **LP (PROPANE) & NATURAL GAS**

MAX WORKING PRESSURE: 80 PSIG



| Item # | Poly Pipe Size | Connection | Length | Box Qty |
|-----------------|----------------------|------------|--------|---------|
| PEFR-12-34M | 1/2" CTS .625 x .090 | 3/4" MIP | 36" | 6 |
| PEFR-12-34-84LM | 1/2" CTS .625 x .090 | 3/4" MIP | 84" | 6 |
| PEFR-34M | 3/4" IPS SDR 11 | 3/4" MIP | 36" | 6 |
| PEFR-01M | 1" IPS SDR 11 | 1" MIP | 36" | 6 |
| PEFR-0114M | 1 1/4" IPS SDR 11 | 1 1/4" MIP | 36" | 2 |
| PEFR10-0114M | 1 1/4" IPS SDR 10 | 1 1/4" MIP | 36" | 2 |
| PEFR-015M | 1 1/2" IPS SDR 11 | 1 1/2" MIP | 36" | 2 |
| PEFR-02M | 2" IPS SDR 11 | 2" MIP | 36" | 2 |

Pro-Flex [™]
Traditional CSST

FlakJacket ™ Arc-Resistant CSST HearthMaster

Fireplace & Log Lighter

Valves, Bars etc.

Pro-Poly " Underground Gas Piping System



www.proflexcsst.com

877-798-6291

sales@proflexcsst.com