
# WALL HEATERS

## **GFR SERIES** FAN-FORCED WALL HEATER



#### **IDEAL SPACES**

- Bedrooms
- Living/Family Rooms
- Kitchens
- Bathrooms
- Basements

#### COLORS

White

### DIMENSIONS

- Grille: 7-3/4"H x 16-7/8"W x 7/8"D
- Back Box: 4-5/8"H x 14-3/8"W x 4-3/8"D

### **TEMP RANGE**

• 40°- 85°F

#### CFM

**50** 





- Conference Rooms
- Hallways
- Lobbies
- Waiting Rooms



- Patented CLIP-N-FIT<sup>®</sup> feature allows installer to change the desired wattage output without moving the jumper wire
- Contemporary register-style grille that blends with any residential or commercial appeal
- Tangential blower for whisper-quiet operation
- Multiple safety features for overheat prevention
- Dual Protection: thermal cutout with indicator light and one time thermal fuse
- Permanently lubricated fan motor and dust-protected bearings
- Simple 3-piece construction makes installation easy



## **GFR SERIES** FAN-FORCED WALL HEATER

| MODELS & SPECIFICATIONS |                 |       |                    |                  |                |                 |  |
|-------------------------|-----------------|-------|--------------------|------------------|----------------|-----------------|--|
| CATALOG NO.             | UPC             | VOLTS | WATTS              | AMPS             | BUILT IN THERM | SHIP WT. (LBS.) |  |
| GFR1500F                | 6 85360 03368 6 | 120   | 1500/1125/750/375  | 12.5/9.4/6.3/3.1 | No             | 10              |  |
| GFR2004F                | 6 85360 03372 3 | 240*  | 2000/1500/1000/500 | 8.3/6.3/4.2/2.1  | No             | 10              |  |
| GFR2404F                | 6 85360 03375 4 | 240*  | 2400/1800/1200/600 | 10.0/7.5/5.0/2.5 | No             | 10              |  |
| GFR1500T2F              | 6 85360 03369 3 | 120   | 1500/1125/750/375  | 12.5/9.4/6.3/3.1 | Double Pole    | 11              |  |
| GFR2004T2F              | 6 85360 03374 7 | 240*  | 2000/1500/1000/500 | 8.3/6.3/4.2/2.1  | Double Pole    | 11              |  |
| GFR2404T2F              | 6 85360 03377 8 | 240*  | 2400/1800/1200/600 | 10.0/7.5/5.0/2.5 | Double Pole    | 11              |  |

NOTE: For wall mounting only. Do not install back box closer than 4 in.from floor, 6 in. from adjacent walls and 36 in. from the ceiling. Do not install heater behind towel rack, behind door, in floor, in closet, in ceiling or where airflow may be obstructed. To insure proper operation, maintain 5 ft. minimum clearance to furniture or other objects placed directly in front of the heater. \*Will operate on 208V at 75% of rated wattages. For installations over 7,500 ft. above sea level we recommend using models under 1500 watts. "T2F" Model are complete heater assemblies with grille, back box, and thermostat.

| ACCESSORIES    |                 |   |                      |  |  |  |
|----------------|-----------------|---|----------------------|--|--|--|
| CATALOG<br>NO. | UPC             | DESCRIPTION                                 | SHIP<br>WT.<br>(LBS) |  |  |  |
| GFRBB          | 6 85360 03363 1 | Single Backbox For GFR<br>Series Heater     | 2                    |  |  |  |
| GFRBB6         | 6 85360 03364 8 | Multi-Pack Backbox<br>(6Pcs)                | 10                   |  |  |  |
| QFGTSP         | 6 85360 03362 4 | Single-Pole Thermostat<br>(Field-Installed) | 1                    |  |  |  |
| QFGTDP         | 6 85360 05925 9 | Double-Pole Thermostat<br>(Field-Installed) | 1                    |  |  |  |
| GFRSM          | 6 85360 05926 6 | Surface Mounting Frame                      | 2                    |  |  |  |

