



# Long Life Ambient CO Detector



## Functions

- Measures: CO 1 to 999 ppm

## Features

- Preset alarms
- 3-Color warning light
- Audible alert
- MAX capture
- Data hold
- Low battery indicator
- CO detection 1 to 999 ppm
- Backlit display
- One button auto zero
- 3-Year limited warranty

## Applications

CO detection for contractors working in environments with potentially high CO concentrations  
First responder responsible for plant safety  
Confirm implementation of government standards for CO exposure





### Includes

- CO Detector (C071A)
- Holster w/ Belt clip
- Battery (9V)
- Owners Manual (17086)

### Specifications

Range	0 - 999 ppm
Resolution	1 ppm
Accuracy	±(3% of reading + 1 ppm)
Visual	Green 2 - 9 ppm Yellow 10 - 34 ppm Red > 35 ppm
Audible	>35 ppm increasing frequency w/concentration
Battery	9V standard alkaline
Ambient Temp	32° to 104°F (0° to 40°C)

### Exposure to CO: Important Numbers To Remember:

- 9 PPM Max allowable exposure for living area (ASHRAE standard)
- 35 PPM Max exposure for 8 hr work day (OSHA)
- 800 PPM Symptoms within 45 minutes - Death within 2 to 3 hrs
- 12,800 PPM Death within 1-3 minutes

### Downloads



**Manual**



**Data Sheet**

H25-947



Made in UK