

















Measuring Program	testo 115i* (Temperature Clamp)	testo 605i (Thermohygrometer)	testo 552i (Digital Vacuum Gauge)	testo 560i (Digital Refrigerant Scale and Intelligent Valve)	testo 915i* (TC Type K Temperature)
Superheat / Subcooling					
Evacuation					
Pressure Leak Test					
Target Superheat					
Compressor DLT					
Delta T					
Refrigeration Filling					

**One for all.
The testo Smart App.**

All measurement applications on your smartphone – and much more: guided programs take you step by step through measurements, and help you evaluate and document results faster, including sending measurement data by e-mail.

- All in one: One App for all Bluetooth®-enabled Testo measuring instruments
- Quick and easy: Measurement menus for numerous applications provide optimum support in configuring and carrying out the measurement
- Graphically visualized presentation of measurement values
- Create digital measurement reports including photos as PDF/CSV files on site and send via e-mail



Download now
free of charge
For Android and IOS

* testo 115i and testo 915i Temperature Smart Probes can be used interchangeably (ex: For **Delta T**, one testo 115i, and one testo 915i may be used).

* testo Smart Digital Manifolds with wired temperature clamps can be used with, or in place of, a testo 115i or testo 915i.

(ex: For **Target Superheat**, one testo 550s with temperature clamps, and two testo 605i can be used.)