



## Model: AJA4492AXD

---

### Product Description

**Type:** Reciprocating  
**Application:** HBP - High Back Pressure  
**Refrigerant:** R-12  
**Voltage/Frequency:** 208-230V ~ 60Hz 200V ~ 50Hz  
**Version:** N/A

---

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	230V ~ 60HZ	9150	2306	2681	1220	7.5	1.89	2.2	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

#### General

**Evaporating Temp. Range:** -6.7°C to 12.8°C (20°F to 55°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 50  
**Weight Unit of Measure:** LB  
**Displacement (cc):** 25.95  
**Oil Type:** Synthetic Alkylate  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 664

#### Electrical

**Voltage Range (50 Hz):** 180-220  
**Voltage Range (60 Hz):** 187-254  
**Locked Rotor Amps (LRA):** 41.8  
**Rated Load Amps (RLA 50 Hz):** 0  
**Rated Load Amps (RLA 60 Hz):** 7  
**Max. Continuous Current (MCC in Amps):** 10.1  
**Motor Resistance (Ohm) - Main:** 1.62  
**Motor Resistance (Ohm) - Start:** 11.58  
**Motor Type:** CSIR  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

cURus Recognized