VALVECORE

A31999

FEATURES

1/4" valve core			\mathbb{R}^{2}
Positive stop valve core for A/C system valves			– Plunger Pin
Operating pressure 800 psi			(Nickel Plated Brass)
Continuous operating temp -20° to 220° F (-28° to 104° C)			
Nickel plated brass			
Teflon barrel gasket seal		rainless Steel)	
Neoprene cup washer			
Installation torque 3 to 5 in/lbs Valve Core Compatible Core Chambers: - ISO standard 7442			
- T&R Standard Bore Chamber No. 1 - AHRI Standard 720			— Barrel Gasket
A32004 Valve Core Tool			(Black Teflon)
A31999 1/4" Valve Core A32008			— Barrel Sheet Metal (Nickel Plated Brass)
Valve Core Torque Tool			
JUSTBETTER Cup Washer (Neoprene)		 Plunger Cup (Nickel Plated Brass) 	
PART NO. QTY. DESCR	RIPTION		
A32004 1 1/4" \	Valve core tool with storage for 6 valve cores		
A32008 1 Valve	A32008 1 Valve core torque tool		
A31999-25 25 1/4" \	Valve cores		
A31999-100 100 1/4" \	Valve cores		MADE IN

INDUSTRIES

WWW.JBIND.COM 800.323.0811 SALES@JBIND.COM

JB

