

811R Small Diameter

APOLLOPRESS® Press End Copper Reducing Outlet Tee
CxCxC (3/4"x3/4"x1/2" through 2"x2"x1-1/2")

SUBMITTAL SHEET

"Apollo" Flow Controls



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

DESCRIPTION

The APOLLOPRESS® 811R Small Diameter Press Reducing Outlet Tee features a lead free dezincification resistant copper body and an EPDM o-ring. APOLLOPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly made in the USA.

FEATURES

- Lead Free Construction
- Ridgid® XL Press Tool Compatible
- Leak Before Press® Technology
- Made in USA

PERFORMANCE RATING

- Maximum Pressure: 300 psi
- Temperature Range: 32°F to 250°F depending on application

STANDARD MATERIALS LIST

Body	UNS C12200 Copper
O-Ring	EPDM
Lubrication	Silicone, ANSI/NSF-61 Listed

APPROVALS

- UPC, cUPC & IPC
- IAPMO PS 117-2016 & TIL MSE-13
- NSF/ANSI 61 - Water Quality
- NSF/ANSI 372 - Lead Free


APOLLOPRESS®

- Small Diameter Sizes 3/4"x3/4"x1/2" through 2"x2"x1-1/2"
- Model 811R, Reducing Outlet Tee

APOLLOPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

DIMENSIONS

ITEM NO.	MODEL & SIZE (IN.)	DIMENSIONS (IN.)									WT. (LB.)
		A	A1	B	B2	C	C3	HEIGHT	WIDTH	DEPTH	
10077745	811 3/4x3/4x1/2 CU CxCxC TEE	1.59	0.69	1.59	0.69	1.38	0.63	2.00	3.18	1.24	0.290
10077748	811 1 1/4x1 1/4x1/2 CxCxC TEE	1.68	0.65	1.68	0.65	1.68	0.93	2.55	3.36	1.74	0.460
10077749	811 1 1/4x1 1/4x3/4 CxCxC TEE	1.80	0.77	1.80	0.77	1.79	0.89	2.66	3.60	1.74	0.510
10077750	811 1 1/2x1 1/2x1 CxCxC TEE	1.91	0.88	1.91	0.88	1.80	0.90	2.67	3.82	1.74	0.565
10077751	811 1 1/2x1 1/2x3/4 CxCxC TEE	1.90	0.47	1.90	0.47	1.85	1.10	2.90	3.80	2.11	0.715
10077752	811 1 1/2x1 1/2x3/4 CxCxC TEE	2.09	0.66	2.09	0.66	2.04	1.14	3.09	4.18	2.11	0.805
10077753	811 1 1/2x1 1/2x1 CxCxC TEE	2.17	0.74	2.17	0.74	2.08	1.18	3.13	4.34	2.11	0.845
10077754	811 1 1/2x1 1/2x1 1/4 CxCxC TEE	2.29	0.86	2.29	0.86	2.16	1.13	3.21	4.58	2.11	0.935
10077746	811 1x1x3/4 CU CxCxC TEE	1.59	0.69	1.59	0.69	1.54	0.79	2.28	3.18	1.49	0.365
10077747	811 1x1x3/4 CU CxCxC TEE	1.75	0.85	1.75	0.85	1.65	0.75	2.39	3.50	1.49	0.430
10077755	811 2x2x1/2 CxCxC TEE	2.13	0.55	2.13	0.55	2.05	1.30	3.34	4.26	2.58	1.065
10077756	811 2x2x3/4 CxCxC TEE	2.37	0.79	2.37	0.79	2.16	1.26	3.45	4.74	2.58	1.230
10077757	811 2x2x1 CxCxC TEE	2.49	0.91	2.49	0.91	2.20	1.30	3.49	4.98	2.58	1.285
10077758	811 2x2x1 1/4 CxCxC TEE	2.62	1.04	2.62	1.04	2.40	1.37	3.69	5.24	2.58	1.420
10077759	811 2x2x1 1/2 CxCxC TEE	2.72	1.14	2.72	1.14	2.80	1.37	4.09	5.44	2.58	1.600



*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

Customer Service (704) 841-6000
www.apolloflowcontrols.com

This specification is provided for reference only. Conbraco Industries Inc. reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. Please visit apolloflowcontrols.com for the most current information.

