



# Buffer Tanks


*For Mixed Circuits and Microloads*



*Zilmet ZBT Buffer Tanks are the ideal solution to integrate variable demands, small loads and mixed flows in high-efficiency heating and chilled water systems. ZBT Buffer Tanks provide thermal mass and hydraulic separation to minimize cycling, simplify installation and reduce energy use.*

## Features

- Optimal capacity for high efficiency boilers in most residential and light-commercial applications
- Compact footprint, flush-mount fittings and side-facing sensor well for a streamlined installation
- Air vent, drain and temperature sensor ports
- Hardware kit includes bottom legs and wall-mount brackets for installation flexibility
- Closed-cell urethane insulation and bonded jacket eliminate condensation problems in chilled-water applications



## Specifications

Max System Pressure:	60 psig
Max Temperature:	200° F
Fluid Compatibility:	Water or Glycol Mix up to 50%
Tank Material:	Welded Steel
Warranty:	5 Years

## Dimensions

<b>Model</b>	<b>Volume Gal</b>	<b>Diameter Inches</b>	<b>Height* Inches</b>	<b>System Connections</b>	<b>Vent &amp; Drain Tappings</b>	<b>Sensor Port</b>
<b>ZBT-7</b>	7	11.4	36.4	1" NPTF	3/4" NPTF	1/2" NPTF
<b>ZBT-14</b>	14	14.2	39.7	1-1/4" NPTF	3/4" NPTF	1/2" NPTF
<b>ZBT-21</b>	21	18.5	35.1	1-1/4" NPTF	1-1/4" NPTF	1/2" NPTF
<b>ZBT-28</b>	28	18.5	42.2	1-1/4" NPTF	1-1/4" NPTF	1/2" NPTF

\*Tank height without accessories. Add 4" when leg kit is installed.

