


SUBMITTAL SHEET

8733-4 Small Diameter Series APOLLOXPRESS® Press End Brass Union CxM (N.P.T.) (½" through 2")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	



DESCRIPTION

The APOLLOXPRESS® 8733-4 Small Diameter Press Brass Union features a Lead-Free dezincification resistant brass body and an EPDM O-Ring. Our Small Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

FEATURES

- Lead-Free Construction
- Leak-Before-Press Technology
- Male N.P.T. per ANSI/ASME B1.20.1
- Compatible with Pro-Press™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

APOLLOXPRESS

- Small Diameter Sizes ½" through 2"
- Model 8733-4, Brass Union CxM (N.P.T.)

PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: 0°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

APPROVALS


- NSF/ANSI NSF 61 ~ Water Quality
- NSF/ANSI NSF-372 ~ Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

STANDARD MATERIALS

Part Name	Material
Body	UNS C27451 Brass
O-Ring	EPDM
Lubrication	Silicone, ANSI/NSF-61 Listed

DIMENSIONS

Item No.	Description	Dimension (in.)								(lb.)
		A	B	C*	D**	E*	Height	Width	Depth	
10075884	8733-4 ½ CxM	2.90	1.26	0.76	2.15	0.76	1.26	2.90	1.26	0.30
10075886	8733-4 ¾ CxM	3.42	1.52	0.92	2.51	0.92	1.52	3.42	1.52	0.50
10075888	8733-4 1 CxM	3.74	1.94	0.92	2.83	0.92	1.94	3.74	1.94	0.82
10075890	8733-4 1¼ CxM	3.78	2.19	1.04	2.73	1.04	2.19	3.78	2.19	0.99
10075892	8733-4 1½ CxM	3.73	2.45	1.43	2.30	1.43	2.45	3.73	2.45	1.36
10075894	8733-4 2 CxM	4.24	3.12	1.59	2.65	1.59	3.12	4.24	3.12	1.96



* Tolerance +/- .045"
** Tolerance +.09 / -.03

Elkhart Products Corporation
1255 Oak Street, Elkhart, IN 46514
www.elkhartproducts.com | (574) 264-3181

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.

