

# One-Way Cassette Ductless System

Indoor Model: **40MCCAQ09XA3**

## Submittal Data

Job Data:  Location:

Buyer:  Buyer P.O. #:  Carrier #:

Unit Number:  Model Number:

Performance Data Certified By:  Date:



### STANDARD FEATURES:

- Designed to be mounted between 16" joists
- Dual Capacity capability
- Modes: Cool, Heat, Dry, Fan, Auto
- Turbo Mode
- Four fan speeds
- Sleep Mode
- ECO Mode
- Quiet indoor operation
- Aluminum Golden Hydrophilic pre-coated fins

### CONTROLS:

- Wireless Remote Controller included with indoor unit

System	Size	6/9*	
	Indoor Model	40MCCAQ09XA3	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	3
Controls	Wireless Remote Controller (°F/°C Convertible)	Standard	
	Wired Remote Controller (°F/°C Convertible)	Optional	
Operating Range	Cooling Indoor DB Min -Max	°F(°C)	60~90 (16~32)
	Heating Indoor DB Min -Max	°F(°C)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	3/8 (9.52)

\*Refer to the installation instructions for capacity setting

Indoor Coil	Face Area	Sq. Ft.	2.81
	No. Rows		2
	Fins per inch		20
	Circuits		2
Indoor	Unit Width	in (mm)	50.31(1278)
	Unit Height	in (mm)	8.98(228)
	Unit Depth	in (mm)	13.19(335)
	Net Weight	lbs (kg)	43.87(19.9)
	Number of Fan Speeds		4
	Airflow (lowest to highest)	CFM	235/259/294/341
	Sound Pressure (lowest to highest)	dB(A)	35/37/38/40
	Air throw Data	ft (m)	22.0 (6.7)
	Moisture removal	Pint/h (L/h)	2.16 (1.02)
Field Drain Pipe Size O.D.	in (mm)	3/8 (9.52)	

Performance may vary based on the outdoor unit matched to. See compatible outdoor units pages for Performance Data.  
For Compatibility See Product Data

# Accessories

KSACN0701AAA	Wired Remote Control 7 Day Programmable
KSACN0101AAA	Wired Remote Control with Timer Function
KSAIF0601AAA	Wi-Fi™ Kit
KSAIC0301230	24V Interface Kit 230V

## Construction View

Indoor Model: **40MCCAQ09XA3**

