## Honeywell

# HE105 & HE205

### WHOLE HOME BYPASS HUMIDIFIER

#### SUBMITTAL SHEET

Job Name	
Engineer	
Mechanical Contractor	
Contractor's P.O. No.	
Representative	
Notes	

Model(s)			
HE105	Qty.	Notes	
HE205	Qty.	Notes	
Approval			
Service			
Tag No.			



#### APPLICATION

The Honeywell Whole-Home Bypass Humidifier combines the versatility, quality, efficiency, and performance with the ease of installation and maintenance, reliability, and value of an evaporative humidifier. Available in two configurations, 12 GPD and 17 GPD, each humidifier comes with the H8908 humidistat and 24V transformer. Other models come with additional kit.

#### INCLUDED IN THE BOX

- Humidifier
- H8908 Humidistat
- Plug-in transformer

#### "C" MODELS ALSO INCLUDE

- 6 in. dia. bypass ducting (24 in.)
- 18-gauge thermostat wire (20 ft.)
- 1/4 in. (6.35 mm) OD feed water tubing (20 ft.)
- 1/2 in. (12.7 mm) ID drain tubing (10 ft.)
- Saddle valve

#### COMPLIMENTARY LABEL OPTION

These labels offer three lines of customized white text printed on a gray sticker that closely matches the Honeywell label on the product. This is a great cost-free opportunity to advertise your business and services.

Up to 3 lines of text/19 maximum characters per line.

Line 1:	
Line 2:	
Line 3:	

Simply complete this form and email it (along with your company logo) to **contractorpro@honeywell.com** with your contractor or distributor information as well as ship-to information.

#### To learn more about the customer label program:

For more information please contact Honeywell Utility Solutions at **(800) 345-6770 (ext. 615).** 

Home and Building Technologies In the U.S.: Honeywell. 1985 Douglas Drive North Golden Valley, MN 55422 customer.honeywell.com

U.S. Registered Trademark
2017 Honeywell International Inc.
33-00247-02 M.S. Rev. 01-17
Printed in United States

SPECIFICATIONS	
Operating Ambient	41 to 113 °F (5 to 45 °C)
Temperature	
Power Supply	24 VAC / 60 Hz
Power Consumption	7 Watts with 24 Vrms
Water Pressure	40 to 120 psi.
Orifice Output	.02 in. (0.5 mm)
Flow Rate at Nozzle:	4.7 GPH (18 L/hr.) under 120 psi
Size	HE105:
length × width ×	15.16 × 16.57 × 9.47 in.
depth	(385 × 421 × 240 mm)
	HE205:
	18.30 × 17.11 × 9.59 in.
	(465 × 434 × 243 mm)
Duct Opening	HE105: 9.43 × 9.28 in.
H×W	(240 × 236 mm)
	<b>HE205:</b> 12.63 × 9.68 in.
	(321 × 246 mm)
Replacement Pad	HE105: HC22
	HE205: HC26
Pad Size	<b>HE105:</b> 10 × 9.5 × 1.5 in.
	(254 × 241 × 38.1 mm)
	<b>HE205:</b> 13.125 × 10 × 1.5 in.
	(333 × 254 × 38.1 mm)
Evaporation	HE105: 12 GPD
Output	HE205: 17 GPD

Complimentary Label Style Example:





33-00247-02