

SINGLE Pipes



Description	Part #	Qty
32mm Single Insulated Pex 90mm Outer Jacket	H9032	1
1-1/4" 40mm Single Insulated Pex 140mm Outer Jacket	H14040	1
1-1/2" 50mm Single Insulated Pex 140mm Outer Jacket	H14050	1
2" 63mm Single Insulated Pex 160mm Outer Jacket	H16063	1
2-1/2" 75mm Single Insulated Pex 160mm Outer Jacket	H16075	1
3" 90mm Single Insulated Pex 200mm Outer Jacket	H20090	1
4" 110mm Single Insulated Pex 200mm Outer Jacket	H200110	1

DOUBLE Pipes



Description	Part #	Qty
28mm Double Insulated Pex 140mm Outer Jacket	HD1401	1
32mm Double Insulated Pex 140mm Outer Jacket	HD14032	1
1-1/4" 40mm Double Insulated Pex 160mm Outer Jacket	HD16040	1
1-1/2" 50mm Double Insulated Pex 160mm Outer Jacket	HD16050	1
2" 63mm Double Insulated Pex 200mm Outer Jacket	HD20063	1

NPT Connectors



Description	Part #	Qty
32mm NPT Pex Connector	HC32/1	1
1-1/4" NPT 40mm Pex Connector	HC40/1.25M	1
1-1/2" NPT 50mm Pex Connector	HC50/1.5M	1
2" NPT 63mm Pex Connector	HC63/2M	1
2-1/2" NPT 75mm Pex Connector	HC75/2.5M	1
3" NPT 90mm Pex Connector	HC90/3M	1
4" NPT 110mm Pex Connector	HC110/4M	1

Operating Range

- Pressures of up to 87 Psi in heating applications with PEX piping from 1" to 4" diameter
- Pressure of up to 140 Psi in plumbing applications with PEX piping from 1" to 2 1/2" diameter

Couplings can be combined with other brass accessories to make T- and knee couplings, connecting pieces, etc.